

WAC LIGHTING

Disc 5CCT

Ceiling and Wall Mount

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-306 6"	9CS 2700K/3000K/3500K/4000K/5000K - 90	15W	950	WT White

Example: **FM-306-9CS-WT**

DESCRIPTION

Multiple mid-powered LEDs uniformly illuminate the acrylic diffuser.

FEATURES

- Multiple LED array for uniform illumination
- 5-CCT Switchable between 2700K and 5000K
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast aluminum with white acrylic diffuser
Power:	15W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50,000 Hours
Mounting:	Retrofit over a 5" or 6" recessed can or install over a 3" or 4" junction box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated: White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, ADA, Title 24 JA8 Compliant




FINISHES:



White

LINE DRAWING:



FM-306