WAC LIGHTING

Under Cabinet Strip

Transformers

LU-2420D-P-BK 20 Plug-in Electronic 2.75IN x 1.625IN x 1.125IN LU-2420D-P-WT 60 Transformer 4IN x 2.1875IN x 1.5IN LU-2460D-P-BK 96 100-240V Input 24V 8.8125IN x 2.0625IN x 2.25IN	Model	Max Output Power	Product	LxWxH
LU-24DC060-UNV-RB2 LU-24DC096-UNV-RB2 Plug-in Electronic Transformer 120V Input 24V Output 60W Remote Electronic Transformer 100-277V Input 24V Output 60W Remote Electronic Transformer 100-277V Input 24V Output 60W Remote Electronic Transformer 100-277V Input 24V Output 96W	LU-2420D-P-BK LU-2420D-P-WT LU-2460D-P-BK LU-24DC060-UNV-RB2	20 60	Plug-in Electronic Transformer 100-240V Input 24V Output 20W Plug-in Electronic Transformer 120V Input 24V Output 60W Remote Electronic Transformer 100-277V Input 24V Output 60W Remote Electronic Transformer 100-277V Input 24V	2.75IN x 1.625IN x 1.125IN 4IN x 2.1875IN x 1.5IN

Example: LU-2420D-P-BK

DESCRIPTION

Low Voltage Class 2 electronic transformer designed to be used as a plug-and-play style transformer. Contains a 72" cord with an quick connect. Inherently protected and power limited, protecting the lighting system from both normal and abnormal short circuits. Built-in auto reset, soft start, short and overload circuit protection features. The soft start delayed start feature extends lamp life by delaying the abrupt inrush current to the lamp. Ideal for WAC Lighting under cabinet systems.

FEATURES

- Includes 6' lead wire and live end
- LU-2460D-P-BK : Integral On/Off switch
- 5 year warranty

SPECIFICATIONS

Input: 100-240 VAC,100-277 VAC,120 VAC,50/60HzHz

Dimming: ELV: 100-10%, TRIAC: 100-10%

Rated Life: 50,000 Hours

Finish: Electrostatically Powder Coated: Black, White,

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: UL, cUL, Damp Location Listed



FINISHES:

Fixture Type:

Project:

Location:

Catalog Number:





Black




Under Cabinet Strip

Transformers

Fixture Type:	
Catalog Number:	
Project:	
Location:	

LINE DRAWING:





24V Plug-In

Class 2 Power Supply

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Product	LxWxH	Finish
EN-2420D-P Plug-in Power Supply 120-240V Input 24V Output 20 Watt	2.75IN x 1.625IN x 1.125IN	BK Black WT White

Example: EN-2420D-P-BK

DESCRIPTION

Low Voltage plug-in Class 2 power supply designed to be used as a plug-andplay style transformer. Contains an 72" wire with an open splice. Ideal for WAC Lighting under cabinet systems.

FEATURES

- UL listed Class 2 plug-in power supply
- 6' wire from wall plug to fixture
- Inherently protected and power limited, protecting the lighting system from both normal and abnormal short circuits.
- 5 year warranty

SPECIFICATIONS

Construction Polycarbonate
Input: 100-240VAC,50/60Hz
Finish: White, Black

Standards: UL, cUL



FINISHES:



WAC LIGHTING

Dimmable Remote Power Supply

60\M/96\M 120-277\/AC/24\/DC

υo	VV/96V	<i>I</i> , IZU-	Z//V	AC/24	VD

IVI	oder & Froduct
	EN-24DC060-UNV-RB2 Remote Enclosed Power Supply 100-277VAC Input 24VDC
(utput 60 Watt

EN-24DC096-UNV-RB2 Remote Enclosed Power Supply 100-277VAC Input 24VDC

ture rype.	
talog Number:	
oject:	
cation:	

IxWxH 8.81IN x 2.06IN x 1.25IN 8.81IN x 2.06IN x 1.25IN

Example: EN-24DC060-UNV-RB2

DESCRIPTION

This class 2 and class P, UL & cUL listed enclosed electronic power supply is the perfect solution for wiring multiple low voltage fixtures. Class 2 power supplys are intrinsically safer power supplys because they are compartmentalized to allow no greater than 5 amps of current to be drawn on each compartment. Enclosure cover is easy to remove. Power supply has knockouts on three sides with clips for line voltage wiring. Secondary wiring for class 2 power supplys do not require conduit sheathed cable or clamp wiring techniques. This power supply has a low minimum load requirement of either 3W, 6W, or 9.6W to allow the use of LED products. May be dimmed using a TRIAC or electronic low voltage dimmer.

FEATURES

- Short circuit, over current, over voltage, over temperature protection.
- Dimming with TRAIC/ELV dimmers
- UL Class 2 Output
- High Power factor > 0.9, and THD FCC Part 15 Class B Compliant
- 5 year warranty


SPECIFICATIONS

Input: 100-277 VAC,50/60Hz Dimming: ELV: %, TRIAC: %

Operating Temp: -4°F to 104°F (-20°C to 60°C) Standards: UL, cUL, Damp Location Listed



LINE DRAWING:



VAC LIGHTING

Under Cabinet Str

Accessories

Model & Product

LU-AB Angled Base LU-EC End Caps LU-FB Fixed Base LU-I I-Connector LU-LE06 6" Live End LU-LE72 72" Live End

Fixture Type:

Project: Location:

Catalog Number:

Example: LU-AB

FEATURES

• Replacement Accessories for Under Cabinet Strip Light

SPECIFICATIONS

Standards: UL, cUL, Damp Location Listed



WAC LIGHTING

Portable Power Supply

60W, 120VAC/24VDC

Model & Product
PS-24DC-60P-GE Portable Power Supply 100-277VAC Input 24VDC 60 Watt

Fixture Type:

Catalog Number:

Project:

Location:

L x W x H 4" X 2.25" X 1.5"

Example: PS-24DC-60P-GE

FEATURES

- Input: 120 VAC, 50/60Hz
- Construction: Polycarbonate
- UL listed Class 2 plug-in Power Supply
- Plug-in power supply with on/off switch and 5' cord
- Class 2 output are required for most cabinet listed fixtures
- Inherently protected and power limited, protecting the lighting system from both normal and abnormal short circuits.
- · Driver included
- 5 Year warranty

SPECIFICATIONS

Input: 120VAC,50/60Hz
Rated Life: 50,000 Hours

Mounting: Can be mounted on ceiling or wall in all orientations

Finish: Black

Operating Temp: -4°F to 104°F (-20°C to 40°C)


Standards: UL, cUL, Damp Location Listed, IP20, ADA



FINISHES:



LINE DRAWING:





Portable Power Supply

60W, 120VAC/24VDC

Fixture Type:		
Catalog Number:		
Project:		
Location:		

ACCESSORIES

Model	Description	Finish
LU-40-30-BK	Under Cabinet Strip	Black
LU-40-30-AL	Under Cabinet Strip	Aluminum
LU-40-27-BK	Under Cabinet Strip	Black
LU-40-27-AL	Under Cabinet Strip	Aluminum
LU-20-30-BK	Under Cabinet Strip	Black
LU-20-30-AL	Under Cabinet Strip	Aluminum
LU-20-27-BK	Under Cabinet Strip	Black
LU-20-27-AL	Under Cabinet Strip	Aluminum
LU-08-30-BK	Under Cabinet Strip	Black
LU-08-30-AL	Under Cabinet Strip	Aluminum
LU-08-27-BK	Under Cabinet Strip	Black
LU-08-27-AL	Under Cabinet Strip	Aluminum