

# WAC LIGHTING

## Kenric 3.5" 5CCT

### Round Trimless Adjustable Downlight

| Model  | Beam | Color Temp & CRI                         | Lumens | CBCP | Finish   |
|--------|------|------------------------------------------|--------|------|----------|
| R3JRAL | W 36 | CS<br>2700K/3000K/3500K/4000K/5000K - 90 | 1450   | 3430 | WT White |

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Example: **R3JRAL-WCS-WT**

#### DESCRIPTION

The Kenric LED recessed luminaire offers an All-In-One 5-CCT adjustable white color temperature range from warm 2700K to cool 5000K. Easy to install with rotatable multi-axis 360-degree horizontal and 30-degree vertical aimability, this low-profile fixture is constructed with die-cast aluminum and a white powder coat trim. Choose between round and square trim and trimless styles with deeply regressed LED for superior glare control. A single fixture provides both downlight and adjustable functions that deploy up to 1450 lumens with a 90 CRI for true-to-life color rendering.



#### FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Sold as remodel, but new construction frame available
- Driver included
- 5 year warranty

#### SPECIFICATIONS


|                           |                                                                  |
|---------------------------|------------------------------------------------------------------|
| <b>Construction</b>       | Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver Box     |
| <b>Power:</b>             | 14.5W                                                            |
| <b>Input:</b>             | 120-277 VAC, 50/60Hz                                             |
| <b>Dimming:</b>           | ELV: 100-5% , 0-10V: 100-5% , TRIAC: 100-5%                      |
| <b>Light Source:</b>      | Integrated LED                                                   |
| <b>Lens:</b>              | TIR Lens                                                         |
| <b>Rated Life:</b>        | 50,000 Hours                                                     |
| <b>Mounting:</b>          | Stainless steel retention springs secures fixture to ceiling     |
| <b>Cut Out:</b>           | 4.5"                                                             |
| <b>Finish:</b>            | Electrostatically Powder Coated: White                           |
| <b>Ceiling Thickness:</b> | 1/2" - 1 1/2"                                                    |
| <b>Operating Temp:</b>    | -4°F to 104°F (-20°C to 40°C)                                    |
| <b>Standards:</b>         | ETL, cETL, Energy Star 2.0, Title 24 JA8 Compliant, Airtight, IC |

#### FINISHES:



White

#### LINE DRAWING:



WAC LIGHTING

Kenric 3.5" 5CCT

Round Trimless Adjustable Downlight

Fixture Type:

Catalog Number:

Project:

Location:

ACCESSORIES

|                                                                                   | Model      | Description      | Finish |
|-----------------------------------------------------------------------------------|------------|------------------|--------|
|  | R3JB-FRAME | Kenric 3.5" 5CCT |        |