

# **Lotos R Retrofit**

## Adjustable Downlight 5CCT

,			
Model Beam	Color Temp & CRI	Lumens CBCP	Finish
R6DRAK A	9CS 2700K/3000K/3500K/40 000K - 90	000K/5 1270 1891	BK Black WT White

Example: R6DRAK-A9CS-BK

#### **DESCRIPTION**

Versatile and multifunctional, the Lotus R Downlights retrofit into 6-inch housings and are field adjustable up to 50 degrees in the regressed trim for quality, glare-free illumination. Offered as an All-In-One Five CCT Selectable luminaire, Lotos is ideal for recessed applications in multifamily homes, hotels, senior living and apartment buildings.

#### **FEATURES**

- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Installs into most standard 6" recessed cans
- Driver concealed within the fixture
- 5 year warranty

#### **SPECIFICATIONS**

**Construction** Steel with frosted TIR lens

Power: 13W

**Input:** 120 VAC,50/60Hz

**Dimming:** ELV: 100-5%, TRIAC: 100-5%

Light Source: Integrated LED
Lens: TIR Lens
Rated Life: 50,000 Hours

**Mounting:** Retrofit over a 6" recessed can

Finish: Electrostatically Powder Coated: Black, White

**Operating Temp:** -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Wet Location Listed, Title 24 JA8 Compliant, Airtight,

IC




#### **FINISHES:**

Fixture Type:

Project:

Location:

Catalog Number:



### LINE DRAWING:

